

# POWER UP WITH TORO®!

**NEW FOR WINTER 2010!**

**QUICK STICK®  
CHUTE CONTROL**



**26" CLEARING  
WIDTH**

**POWER MAX  
AUGER SYSTEM**

**NEW!  
POWER THROW® 722E**



**BRIGGS & STRATTON®  
205cc OHV ENGINE**

**22" CLEARING  
WIDTH**

**POWER THROW  
AUGER SYSTEM**



**NEW!  
POWER CLEAR® 210E**  
Electric Start



**NEW!  
1800 POWER CURVE®**  
Electric Snowthrower


















**BETTER VALUE!  
POWER MAX® 826 OXE**  
Now equipped with freewheel steering!

**TORO®**











**Count on it.**


# TWO-STAGE SPECIFICATIONS

MODELS	Power Throw® 722E	Power Max® 7260E	Power Max 8260XE	Power Max 8280XE	Power Max 10280XE	Power Max 11280XE
PERFORMANCE	38608	38614	38624W	38634	38644	38654
Capacity / Minute*	Up to 1800 lbs. 	Up to 1900 lbs.	Up to 1900 lbs. 	Up to 2000 lbs. 	Up to 2100 lbs. 	Up to 2200 lbs.
Throw Distance	Up to 30' 	Up to 45'	Up to 45'	Up to 45'	Up to 45'	Up to 45'
Clearing Width	22" 	26"	26" 	28"	28"	28"
Drive System	Friction Disc	Friction Disc 	Friction Disc w/ Freewheel Steering	Friction Disc w/ Freewheel Steering	Friction Disc w/ Freewheel Steering	Friction Disc w/ Freewheel Steering
ENGINE						
Engine	205cc Briggs & Stratton® OHV 4-Cycle	205cc Briggs & Stratton OHV 4-Cycle 	250cc Briggs & Stratton OHV 4-Cycle	250cc Briggs & Stratton OHV 4-Cycle 	305cc Briggs & Stratton OHV 4-Cycle 	342cc Briggs & Stratton OHV 4-Cycle 
Starter	Electric	Electric	Electric	Electric	Electric	Electric
Fuel Capacity	2 Quarts	3.2 Quarts	3.2 Quarts	3.2 Quarts	3.2 Quarts	3.2 Quarts
USER-FRIENDLY FEATURES						
Chute Control	Remote Chute Crank 	Quick Stick®	Quick Stick	Quick Stick	Quick Stick	Quick Stick
Scraper	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable 	Pivoting
Weight	162 lbs.	210 lbs.	222 lbs.	237 lbs.	257 lbs.	257 lbs.
Warranty**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited

 = indicates new model

# SINGLE-STAGE SPECIFICATIONS

MODELS	Power Clear® 180	Power Clear 210	Power Clear 221Q	Power Clear 421Q	CCR™ 2450
PERFORMANCE	38272 / 38282	38587 / 38593	38583 / 38584	38588 / 38589	38515
Capacity / Minute*	Up to 1100 lbs. 	Up to 1700 lbs.	Up to 1700 lbs. 	Up to 1800 lbs.	Up to 1700 lbs.
Throw Distance	Up to 25' 	Up to 30'	Up to 30' 	Up to 35'	Up to 30'
Clearing Width	18" 	21"	21"	21"	20"
Auger System	Power Curve® Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor
ENGINE					
Engine	Toro® 87cc 4-Cycle OHV 	R*tek 141cc 2-Cycle	R*tek 141cc 2-Cycle 	Toro 163cc 4-Cycle OHV	R*tek 141cc 2-Cycle
Starter	Recoil / Electric	Recoil / Electric	Recoil / Electric	Recoil / Electric	Recoil
Fuel Capacity	1.4 Quarts	1.1 Quarts	1.1 Quarts	1.1 Quarts	1.0 Quarts
Drive System	Rotor Propelled	Power Propel Self Propel 	Power Propel Self Propel	Power Propel Self Propel	Rotor Propelled
USER-FRIENDLY FEATURES					
Chute Type	Curved with Zip Deflector	Chute and Deflector Handle 	Square with Zip Deflector	Square with Zip Deflector	Chute and Deflector Handle
Chute Control	Chute Mounted Handle	Chute Mounted Handle 	Quick Shoot	Quick Shoot	Chute Mounted Handle
Weight (Recoil / Electric)	54 lbs. / 58 lbs	73 lbs. / 75 lbs.	74 lbs. / 76 lbs.	84 lbs. / 89 lbs.	71 lbs.
Warranty**	2-Year Full	2-Year Full	2-Year Full	2-Year Full	2-Year Full

 = indicates new model



©2010 The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \*Capacity and throw distance will vary with conditions. \*\*See toro.ca or your dealer for warranty details. 490-8117NA\_CEN 03/10