

TORO

Count on it.

POWER CLEAR®

SINGLE-STAGE SNOWBLOWERS



Our best-selling snowblower. Lightweight and easy to maneuver, this single-stage machine can cut up to a third of your snowthrowing time.*

**Compared to a comparably equipped two-stage unit.*

IDEAL FOR:

- ▶ Urban- and suburban-size driveways
- ▶ Concrete and asphalt surfaces
- ▶ Medium to heavy snowfalls

INNOVATIVE FEATURES:

- ▶ Quick Shoot Chute Control
- ▶ Power Propel Self-Propel
- ▶ Power Curve® Technology
- ▶ Choice of R*tek® 2-Cycle or Toro® 4-Cycle Engine

Guaranteed to Start (GTS) on the first or second pull for 2 years or Toro will fix it for free (select models).**



SINGLE-STAGE SNOWBLOWERS

Power Clear® 180
38272 / 38282

Power Clear 210
38587 / 38593

Power Clear 221Q
38583 / 38584

Power Clear 421Q
38588 / 38589

CCR™ 2450
38515

PERFORMANCE					
Capacity / Minute*	Up to 1100 lbs. / 500 kg	▶ Up to 1700 lbs. / 773 kg	Up to 1700 lbs. / 773 kg	▶ Up to 1800 lbs. / 818 kg	Up to 1700 lbs. / 773 kg
Throw Distance*	Up to 25' / 8 m	▶ Up to 30' / 9 m	Up to 30' / 9 m	▶ Up to 35' / 11 m	Up to 30' / 9 m
Clearing Width	18"	▶ 21"	21"	21"	20"
Auger System	Power Curve® Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor
Snow Cut Depth — 1 Pass	12"	▶ 12.5"	12.5"	12.5"	13.0"
ENGINE					
Engine	Toro® 87cc 4-cycle OHV	▶ R*tek 141cc 2-cycle	R*tek 141cc 2-cycle	▶ Toro 163cc 4-cycle OHV	R*tek 141cc 2-cycle
Starter	Recoil / Electric Start	Recoil / Electric Start	Recoil / Electric Start	Recoil / Electric Start	Recoil
Fuel Capacity	1.4 Quarts / 1.3 L	1.1 Quarts / 1 L	1.1 Quarts / 1 L	1.1 Quarts / 1 L	1.1 Quart / 1 L
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic
Compression Release	Standard	Standard	Standard	Standard	Standard
Governor Auger System	Mechanical	Air-Vane	Air-Vane	Mechanical	Air-Vane
Drive System	Rotor Propelled	▶ Power Propel Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel	Rotor Propelled
USER-FRIENDLY FEATURES					
Chute Type	Curved with Zip Deflector	Curved with Friction Deflector	▶ Square with Zip Deflector	Square with Zip Deflector	Curved with Friction Deflector
Chute Control	Chute-Mounted Handle	Chute-Mounted Handle	▶ Quick Shoot	Quick Shoot	Chute-Mounted Handle
Scraper	Stationary	▶ Pivoting	Pivoting	Pivoting	Stationary
Weight: Recoil / Electric Start	54 lbs. / 58 lbs. 25 kg / 27 kg	72 lbs. / 74 lbs. 33 kg / 34 kg	74 lbs. / 76 lbs. 34 kg / 35 kg	79 lbs. / 83 lbs. 36 kg / 38 kg	71 lbs. / 32 kg
Starting Guarantee**	N/A	2-Year GTS	2-Year GTS	2-Year GTS	2-Year GTS
Warranty**	2-Year Full	2-Year Full	2-Year Full	2-Year Full	2-Year Full

▶ = Enhance or step-up feature.

POWER CLEAR FEATURES



POWER PROPEL SYSTEM

This system takes the work out of snowblowing. An innovative pivoting scraper keeps the rotor in constant contact with the pavement, making the job quicker and easier.



ZIP DEFLECTOR

Throw snow high, low or in-between. The deflector locks in to any angle in less than a second—with just a touch of your hand. (Select models only.)



QUICK SHOOT CONTROL SYSTEM

You can change the chute direction without even slowing down. Just squeeze the trigger and slide the handle-mounted grip to throw snow exactly where you want it. (Select models only.)



ELECTRIC START

Getting started has never been easier. Just plug it in, push a button and go. (Select models only.)

TORO

©2010 The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *Capacity and throw distance will vary with conditions. **See toro.com or your dealer for warranty details.

490-8154 07/10