

TORO

Count on it.

POWER MAX[®] & POWER THROW[®]

TWO-STAGE SNOWBLOWERS



Power Max plows through even the toughest snow – fast. Its commercial-grade design keeps homeowners in mind with its convenient hand controls for easy turning and chute control.

IDEAL FOR:

- ▶ Clearing large or extra-large areas
- ▶ All surface types, including gravel
- ▶ Heavy, wet snowfalls

INNOVATIVE FEATURES:

- ▶ Power Max Auger System
- ▶ Freewheel Power Steering
- ▶ Quick Stick[®] Chute Control
- ▶ One-hand Interlock

If anything goes wrong in the first 3 years under normal use and maintenance, Toro will fix it free.**



TWO-STAGE SNOWBLOWERS

NEW
Power Throw® 722E
38608

NEW
Power Max® 726 OE
38614

NEW
Power Max 826 OXE
38624W

Power Max 828 OXE
38634

Power Max 1028 OXE
38644

Power Max 1128 OXE
38654

PERFORMANCE

Capacity / Minute*	Up to 1800 lbs. / 818 kg	▶ Up to 1900 lbs. / 864 kg	Up to 1900 lbs. / 864 kg	▶ Up to 2000 lbs. / 909 kg	▶ Up to 2100 lbs. / 955 kg	▶ Up to 2200 lbs. / 1000 kg
Throw Distance*	Up to 30' / 9 m	▶ Up to 45' / 13.5 m	Up to 45' / 13.5 m	Up to 45' / 13.5 m	Up to 45' / 13.5 m	Up to 45' / 13.5 m
Clearing Width	22"	▶ 26"	26"	▶ 28"	28"	28"
Drive System	Friction Disc	Friction Disc	Friction Disc	Friction Disc	Friction Disc	Friction Disc
Wheel Clutches	N/A	N/A	▶ Standard	Standard	Standard	Standard
Speeds	3 Forward / 1 Reverse	▶ 6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse
Snow Cut Depth – 1 Pass	17.5"	▶ 21"	21"	21"	21"	21"

ENGINE

Engine	205cc B&S OHV 4-cycle	205cc B&S OHV 4-cycle	▶ 250cc B&S OHV 4-cycle	250cc B&S OHV 4-cycle	▶ 305cc B&S OHV 4-cycle	▶ 342cc B&S OHV 4-cycle
Starter	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start
Fuel Capacity	3.2 Quarts / 3 L	3.2 Quarts / 3 L	3.2 Quarts / 3 L	3.2 Quarts / 3 L	3.2 Quarts / 3 L	3.2 Quarts / 3 L
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Compression Release	Standard	Standard	Standard	Standard	Standard	Standard
Governor Auger System	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical

USER-FRIENDLY FEATURES

Chute Control	Remote Chute Crank	▶ Quick Stick®	Quick Stick	Quick Stick	Quick Stick	Quick Stick
One-Hand Interlock	No	▶ Yes	Yes	Yes	Yes	Yes
Scraper	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	▶ Pivoting
Tires	13"	▶ 15"	15"	15"	15"	15"
Headlight	No	No	▶ Yes	Yes	Yes	Yes
Weight	162 lbs. / 73 kg	220 lbs. / 95 kg	222 lbs. / 103 kg	237 lbs. / 108 kg	257 lbs. / 117 kg	257 lbs. / 117 kg
Warranty**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited

▶ = Enhance or step-up feature.

POWER MAX FEATURES



POWER MAX AUGER SYSTEM

This system reduces clogging and maximizes impeller speed and snowblowing velocity — allowing you to power through heavy snow, deep drifts and compacted berms with ease.



FREEWHEEL POWER STEERING

Turn on a dime with the flex of a finger. Handle-mounted triggers allow you to disengage one or both wheels for effortless steering and maneuverability. (on 28" models)



QUICK STICK® CHUTE CONTROL

An innovative joystick control allows you to change the chute direction quickly and easily, even on the go.



ONE-HAND INTERLOCK

Convenient levers allow one-handed operation, freeing the other hand to shift speeds or adjust the chute without stopping.

TORO

©2010 The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *Capacity and throw distance will vary with conditions. **See toro.com or your dealer for warranty details.

490-8155 07/10